

Description:

Trowel Mastic is a heavily bodied bituminous mastic that is used for filling joints, cracks and splits in roofing and building materials including roofing felt, asphalt, concrete, asbestos cement sheets, metallic guttering and drainpipes. It is resistant to water penetration immediately after application and is ideally suited for maintenance and remedial work.

Colour:

Black.

Preparation:

Ensure that the surface is clean, dry and free from oil, grease, dirt and organic growth. Organic growth such as moss and lichen can be removed using fungicidal wash. Bolt heads on roof sheets should be wire brushed to remove rust before being sealed with Trowel Mastic. Porous surfaces should be primed with Bitumen Primer in order to seal the surface and allow them to dry thoroughly.

Method of Application:

To assist application, tools can be lubricated with white spirit or paraffin. Apply Trowel Mastic by trowel or putty knife, forcing material into cracks and joints and smoothing out on either side. Cracks or joints of more than 3mm should be reinforced with glass fibre scrim and covered with a second application of mastic.

Coverage and Drying:

A typical coverage rate for a 2mm thickness is 2m² per Litre

Drying time depends on weather conditions and film thickness. Heavy applications will result in extended drying times.

Cleaning:

All tools should be cleaned immediately after use with white spirit. Hardened material can be removed by soaking in white spirit.

Shelf Life and Storage:

After use, replace the lid to ensure an airtight seal. Shelf life is indefinite if container is kept sealed and is stored in a dry area at temperatures between 8°C and 25°C.

Health & Safety:

For further regulatory Health & Safety Information please refer to Safety Data Sheet.