

EMERGENCY ROOF & GUTTER SPRAY

Applications

This highly versatile formula is suitable for use on a wide range of construction materials and roofing substrates.

Ideal for:

- Emergency sealing of leaks on flat and pitched roofs
- Waterproofing gutters, gulleys, and drainpipes
- Preventing further water damage from cracks or small openings
- Providing immediate weatherproof protection

Directions for Use

1. Shake the can thoroughly before each use.
2. Test on a small, inconspicuous area first to ensure compatibility, finish, and performance.
3. Ensure the surface is clean and free from dirt, grease, and loose residues. Surfaces should be dry where possible.
4. Hold the can 15–30 cm from the surface and spray evenly over the damaged area using several light coats.
5. In colder conditions, allow 15–20 minutes drying time between coats to build a strong protective layer.

For Larger Cracks or Holes

1. Apply a generous base coat to the repair area.
2. Place reinforcement material such as nylon gauze or scrim over the wet coating.
3. Apply additional coats over the reinforcement until fully sealed.

Product Characteristics

Colour	Black
Odour	Solvent
Application Temp.	Between 5°C and 30°C
Coverage	0.15 to 0.5 m ² depending on application
Flash Points	< -40°C

Ideal for use on:

- Felt
- Bitumen
- Corrugated metal
- Gutters & drainpipes
- Conservatories & windows
- Roof tiles
- Chimneys

Benefits

- Versatile
- Highly water resistant
- Flexible
- Easy to Apply

Precautions for Use: For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).